

**ANJI GUYOU FURNITURE CO., LTD**

BAISHUIWAN INDUSTRY ZONE, TIANHUANGPING TOWN, ANJI COUNTY, HUZHOU, ZHEJIANG, CHINA

The following sample(s) was / were submitted and identified on behalf of the client as:

|                          |                               |
|--------------------------|-------------------------------|
| Sample Description       | CHAIR                         |
| Style / Item No.         | Y-2711-2D / SILVERSTONE       |
| Buyer                    | LETTO BELLO S. L.             |
| Supplier                 | ANJI GUYOU FURNITURE CO., LTD |
| Manufacturer             | ANJI GUYOU FURNITURE CO., LTD |
| Country of Origin        | CHINA                         |
| Country of Destination   | SPAIN                         |
| Sample Receiving Date    | JUN 16, 2017                  |
| Sample Re-submitted Date | JUL 03, 2017                  |
| Test Performing Date     | JUN 16, 2017 TO JUL 19, 2017  |

| Test Result Summary  |           |
|--|-----------|
| Test(s) Requested  | Result(s) |
| UNE-EN 1335-1/AC:2003 (Type C)   | PASS      |
| UNE-EN 1335-2:2009<br>UNE-EN 1335-3:2009<br>Excluding Clause 5 information for use in EN 1335-2. | PASS      |
| <b>Summary:</b>  |           |
| 1. For further details, please refer to the following page(s)                                    |           |

Signed for and on behalf of  
SGS-CSTC Co., Ltd. Anji Branch



David Fan  
Approved Signatory



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No. 301, Sunlight Road, 2 Block, Sunlight Industry Zone, Anji County, Zhejiang Province, China 313300 t (86-572) 5018825 f (86-572) 5018829 www.sgsgroup.com.cn  
中国·浙江·安吉县阳光工业园二区阳光大道301号 邮编:313300 t (86-572) 5018825 f (86-572) 5018829 e sgs.china@sgs.com

**Test Conducted: UNE-EN 1335-1/AC:2003 Office furniture- Office work chair- Part 1: Determination of dimensions**
**Test Result (Chair type C):**

| Test Item  | Test Requirement  | Result |
|--|---|--------|
| Seat height [a]  | Adjustable: min. $\leq 420\text{mm}$ , max. $\geq 480\text{mm}$<br>Adjustment range: $\geq 80\text{mm}$                 | PASS   |
| Seat depth [b]   | Non-adjustable: $\geq 380\text{mm}$   | PASS   |
|  | Adjustable: min. $\leq 400\text{mm}$<br>Adjustment range: no requirement  |        |
| Depth of seat surface [c]  | $\geq 380\text{mm}$   | PASS   |
| Seat width [d]   | $\geq 400\text{mm}$   | PASS   |
| Inclination of seat surface [e]  | Non-adjustable: $-2^\circ - -7^\circ$   | PASS   |
|  | Adjustable: min. $\leq -2^\circ$ , max. $\geq -7^\circ$<br>Adjustment range: no requirement                             |        |
| Height of the back supporting point "S" above the seat surface [f]             | Non-adjustable: 170mm – 220 mm  | NA     |
|  | Adjustable: no requirement<br>Adjustment range: no requirement  |        |
| Height of the back pad [g]   | Adjustable in height: no requirement  | PASS   |
|  | Non-adjustable in height: $\geq 260\text{mm}$   |        |
| Height of the upper edge of the back rest above the seat surface [h]           | $\geq 360\text{mm}$   | PASS   |
| Back rest width [i]  | $\geq 360\text{mm}$   | PASS   |
| Horizontal radius of back rest [k]   | $\geq 400\text{mm}$   | PASS   |
| Back rest inclination [l]  | No requirement  | NA     |
| Length of arm rest [n]   | $\geq 200\text{mm}$   | PASS   |
| Width of arm rest [o]  | $\geq 40\text{mm}$  | PASS   |
| Height of arm rest above the seat [p]  | Non-adjustable: 200mm – 250 mm  | PASS   |
|  | Adjustable: min. $\leq 200\text{mm}$ , max. $\geq 250\text{mm}$   |        |
| Distance from the front of arm rests to the front edge of the seat surface [q] | $\geq 100\text{mm}$   | PASS   |
| Clear width between the arm rests [r]  | $\geq 460\text{mm}$   | PASS   |
| Maximum offset of the underframe [s]   | $\leq X+50$<br>X=The maximum horizontal distance between parts of the upper parts of the chair and the axis of rotation | PASS   |
| Stability dimension [t]  | $\geq 195\text{mm}$   | PASS   |

**Remark:**

1. NA = Not applicable



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Inspection & Testing Services Co., Ltd.  
Anji Branch Harbin

No. 301, Sunlight Road, 2 Block, Sunlight Industry Zone, Anji County, Zhejiang Province, China 313300 t (86-572) 5018825 f (86-572) 5018829 www.sgsgroup.com.cn  
中国·浙江·安吉县阳光工业园二区阳光大道301号 邮编:313300 t (86-572) 5018825 f (86-572) 5018829 e sgs.china@sgs.com

**Test Conducted: UNE-EN 1335-2:2009 Office furniture- Office work chair- Part 2: Safety requirements  
 UNE-EN 1335-3:2009 Office furniture - Office work chair - Part 3: Test methods**

**Test Result:**

| Test Item   | Test Method & Test Requirement   | Test Result |
|---|--|-------------|
| <b>Safety requirements: General design requirements (UNE-EN 1335-2:2009, 4.1)</b>   |  |             |
| Corners and edges, trapping, pinching, and shearing (UNE-EN 1335-2:2009, 4.1.1)   | The chair shall be so designed as to minimize the risk of injury to the user.<br>All parts of the chair with which the user comes into contact, during intended use, shall be so designed that physical injury and damage to property are avoided.<br>These requirements are met when:<br>a) The safety distance of accessible movable parts is either $\leq 8\text{mm}$ or $\geq 25\text{mm}$ in any position during movement<br>b) Accessible corners are rounded with minimum 2 mm radius<br>c) The edges of the seat, back rest and arm rests which are in contact with the user when sitting in the chair are rounded with minimum 2 mm radius<br>d) The edges of handles are rounded with minimum 2mm radius in the direction of the force applied<br>e) All other edges are free from burrs and rounded or chamfered<br>f) The ends of hollow components are closed or capped | PASS        |
| Adjusting devices (UNE-EN 1335-2:2009, 4.1.2)   | Movable and adjustable parts shall be designed so that injuries and inadvertent operation are avoided.<br>It shall be possible to operate the adjusting device from sitting position in the chair.   | PASS        |
| Connections (UNE-EN 1335-2:2009, 4.1.3)   | It shall not be possible for any load bearing part of the chair to come loose unintentionally.   | PASS        |
| Avoidance of soiling (UNE-EN 1335-2:2009, 4.1.4)  | All parts which are lubricated to assist sliding shall be designed to protect users from lubricant stains when in normal use.  | PASS        |
| <b>Safety requirements: Stability during use (UNE-EN 1335-2:2009, 4.3)</b>  |  |             |
| Requirements are fulfilled if the chair does not overbalance when tested according to 7.1.1 to 7.1.7 of UNE-EN 1335-3:2009 with the forces and numbers of cycles according to Table A.1 of this standard. |  |             |
| Front edge overturning (UNE-EN 1335-3:2009, 7.1.1)  | Fix the strap to the chair i.e. the force is applied at the point on the front edge that is furthest from the axis of rotation, and allows the mass $M_1$ of 27 kg to hang freely.   | PASS        |
| Forwards overturning (UNE-EN 1335-3:2009, 7.1.2)  | Apply a vertical force $F_1$ of 600 N acting 60 mm from the front edge of the load bearing structure of the seat at those points most likely to result in overturning. Apply for at least 5 s a horizontal outwards force $F_2$ of 20 N from the point on the seat surface where the vertical force is applied.  | PASS        |



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.  
 Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com  
 No. 301, Sunlight Road, 2 Block, Sunlight Industry Zone, Anji County, Zhejiang Province, China 313300 t (86-572) 5018825 f (86-572) 5018829 www.sgs.com.cn  
 中国·浙江·安吉县阳光工业园二区阳光大道301号 邮编:313300 t (86-572) 5018825 f (86-572) 5018829 e sgs.china@sgs.com

| Test Item  | Test Method & Test Requirement  | Test Result |
|--|---|-------------|
| Forwards overturning for chairs with footrest<br>(UNE-EN 1335-3:2009, 7.1.3)                   | For chairs with footrests repeat the principle of 7.1.2 on the footrest. Apply vertical force $F_1$ of 1100 N acting 60 mm from the front edge of the load bearing structure of the footrest at those points most likely to result in overturning. Apply for at least 5 s a horizontal outwards force $F_2$ of 20 N from the point on the footrest surface where the vertical force is applied.<br>For round cross section ring shaped footrests, the vertical force $F_1$ shall be applied through the centre of the ring cross section.   | NA          |
| Sideways overturning for chair without arm rests<br>(UNE-EN 1335-3:2009, 7.1.4)                | Apply a vertical force $F_1$ of 600 N acting 60 mm from the side edge of the load bearing structure of the seat at those points most likely to result in overturning. Apply for at least 5 s a horizontal sideways force $F_2$ of 20 N outwards from the point on the seat surface where the vertical force is applied.   | NA          |
| Sideways overturning for chair with arm rests<br>(UNE-EN 1335-3:2009, 7.1.5)                   | Apply a vertical force $F_1$ of 250 N acting at a point 100 mm from the fore and aft centre line of the seat at the restrained side and between 175 mm and 250 mm forward of the rear edge of the seat. Apply a vertical downward force $F_2$ of 350 N acting at points on the arm rest at the restrained side up to a maximum 40 mm inwards from the outer edge of the upper surface of the arm rest, but not beyond the centre of the arm rest, and at the most adverse position along its length. Apply a horizontal sideways force $F_3$ of 20 N outwards from the same point for at least 5 s.   | PASS        |
| Rearwards overturning for chairs without back rest inclination<br>(UNE-EN 1335-3:2009, 7.1.6)  | A vertical force $F_1$ of 600 N shall be applied at point "A" and a horizontal force $F_2$ of 192 N shall be applied at point "B".<br>If the back rest pad is pivoting around a horizontal axis above the height of the seat and is free to move, the horizontal force shall be applied on the axis. If height adjustable, the axis shall be set as close as possible to 300 mm above point "A".  | PASS        |
| Rearwards overturning for chairs with back rest inclination<br>(UNE-EN 1335-3:2009, 7.1.7)     | Load the chair with 13 discs so that the discs are firmly settled against the back rest. If the height of the stack of discs exceeds the height of the back rest, prevent the upper discs from sliding off by the use of a light support.   | PASS        |
| <b>Safety requirements: Rolling resistance of the unloaded chair (UNE-EN 1335-2:2009, 4.4)</b> |   |             |
| Rolling resistance of the unloaded chair<br>(UNE-EN 1335-2:2009, 4.4)                          | The unloaded chair shall not roll unintentionally.<br>This requirement is met when:<br>a) the castors are of identical construction;<br>b) the rolling resistance is $\geq 12$ N when tested according to UNE-EN 1335-3:2009, 7.4.<br>The chair shall be placed on the test surface and shall be pushed or pulled over a distance of at least 550 mm. A speed of $(50 \pm 5)$ mm/s shall be maintained over the measuring distance. The force shall be applied at a height of $(200 \pm 50)$ mm above the test surface.<br>Record the force used to push or pull the chair over the distance from 250mm to 500mm as the rolling resistance. | PASS        |



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-TESTING SERVICES  
Inspection & Testing Services  
Anji Branch Harbin

No. 301, Sunlight Road, 2 Block, Sunlight Industry Zone, Anji County, Zhejiang Province, China 313300 t (86-572) 5018825 f (86-572) 5018829 www.sgs.com.cn  
中国·浙江·安吉县阳光工业园二区阳光大道301号 邮编:313300 t (86-572) 5018825 f (86-572) 5018829 e sgs.china@sgs.com

| Test Item  | Test Method & Test Requirement  | Test Result   |           |                  |
|--|---|---------------|-----------|------------------|
| <p><b>Safety requirements: Strength and durability (UNE-EN 1335-2:2009, 4.5)</b><br/>           Requirements are fulfilled when after the tests specified in 7.2.1, 7.2.2, 7.2.6, 7.3.1 and 7.3.2 of UNE-EN 1335-3:2009 with the forces and numbers of cycles according to Table A.2 of this standard:<br/>           e) there are no fractures of any member, joint or component, and<br/>           f) there is no loosening of joints intended to be rigid, and<br/>           g) no major structural element is significantly deformed and the chair fulfils its functions after removal of the test loads<br/>           and when:<br/>           h) after the test in 7.2.3 of UNE-EN 1335-3:2009 with the forces and numbers of cycles according to Table A.2 of this standard, the arm rests show no fracture.</p> |   |               |           |                  |
| Seat front edge static load test (UNE-EN 1335-3:2009, 7.2.1)   | Position the smaller seat loading pad at loading point "F" or "J". Apply a vertical downward force $F_1$ of 1600 N through the centre of the loading pad. Repeat the operation for 10 cycles.   | PASS          |           |                  |
| Combined seat and back static load test (UNE-EN 1335-3:2009, 7.2.2)  | Apply a vertical force $F_1$ of 1600 N at point "A". Keep the seat loaded and apply a force $F_2$ of 560 N at point "B". When fully loaded the force shall act at $90^\circ \pm 10^\circ$ to the back rest plane. Remove the back force and then the seat force. Repeat the operation for 10 cycles.  | PASS          |           |                  |
| Foot rest static load test (UNE-EN 1335-3:2009, 7.2.6)   | Apply a vertical force of 1300 N acting 80 mm from front edge of the load bearing structure of the foot rest at those points most likely to cause failure. For round cross section ring shaped footrests, the force shall be applied through the centre of the ring cross section. If the chair tends to overturn load the seat to prevent overturning and report the load. Repeat the operation for 10 cycles.   | NA            |           |                  |
| Seat and back durability (UNE-EN 1335-3:2009, 7.3.1)   | <p>The seat load shall be applied vertically. The back rest force shall be applied at an angle of <math>90^\circ \pm 10^\circ</math> to the back rest when fully loaded. All chairs shall be tested to steps 1 to 5.<br/>           Chairs with a locking device for seat and/or back rest angle movements shall be tested in step 2 first with the device locked for half of the cycles and then with the device unlocked for the other half of the cycles. In steps 3, 4 and 5 the mechanism shall be set free to move.<br/>           If the back rest pad is pivoting around a horizontal axis and is free to move, the horizontal force shall be applied on the axis. If height adjustable, the axis shall be set as close as possible to 300 mm above point "A". If the axis cannot be adjusted to 300 mm, adjust the force to produce the same bending moment.</p> |               |           |                  |
|  | Step  | Loading point | Force (N) | Number of cycles |
|  | 1   | A             | 1500      | 120000           |
|  | 2   | C             | 1200      | 80000            |
|  |   | B             | 320       |                  |
|  | 3   | J             | 1200      | 20000            |
|  |   | E             | 320       |                  |
| 4  | F   | 1200          | 20000     |                  |
|  | H   | 320           |           |                  |
| 5  | D and G (alternating)   | 1100          | 20000     |                  |



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com  
 No. 301, Sunlight Road, 2 Block, Sunlight Industry Zone, Anji County, Zhejiang Province, China 313300 t (86-572) 5018825 f (86-572) 5018829 www.sgs.com.cn  
 中国·浙江·安吉县阳光工业园二区阳光大道301号 邮编: 313300 t (86-572) 5018825 f (86-572) 5018829 e sgs.china@sgs.com

| Test Item   | Test Method & Test Requirement   | Test Result |
|---|--|-------------|
| Arm rest durability<br>(UNE-EN 1335-3:2009, 7.3.2)                          | Apply simultaneously and cyclically the force of 400 N on each arm rest at points 100 mm behind the foremost point of the arm rest length. Repeat the operation for 60000 cycles.  | PASS        |
| Arm rest downward static load test – central<br>(UNE-EN 1335-3:2009, 7.2.3) | Apply the force to both arm rests simultaneously and vertically at the middle point of the arm rest length and centred side to side.<br>Test force (N): 750 Number of cycles: 5<br>Test force (N): 900 Number of cycles: 5   | PASS        |
| <b>Information for use (UNE-EN 1335-2:2009, 5)</b>                          |  |             |
| Information for use<br>(UNE-EN 1335-2:2009, 5)                              | Each chair shall be accompanied by information for use in the language of the country in which it will be delivered to the end user. It shall contain at least following details:<br>a) Information regarding the intended use;<br>b) Information regarding possible adjustments and chair type;<br>c) Instruction for operation the adjusting mechanisms;<br>d) Instruction for the care and maintenance of the chair;<br>e) Information regarding adjustments;<br>f) Information for chairs with seat height adjustments with energy accumulators that only trained personnel may replace or repair seat height adjustment components with energy accumulators;<br>g) Information on the choice of castors in relation to the floor surface. | NP          |
| <b>Functional tests (UNE-EN1335-3:2009, Annex C)</b>                        |  |             |
| Arm rest downward static load test –front<br>(UNE-EN 1335-3:2009, 7.2.4)    | Apply the force of 450 N to both arm rests simultaneously and vertically acting at 75 mm from the front edge and centred side to side. Repeat the operation for 5 cycles.  | PASS        |
| Arm rest sideways static load test<br>(UNE-EN 1335-3:2009, 7.2.5)           | Apply an outward horizontal force of 400 N to both arm rests simultaneously. Apply the forces to the edge of the arm rest at the point along the arm rest most likely to cause failure but not less than 75 mm from the front or rear edge. Repeat the operation for 10 cycles.  | PASS        |
| Swivel test<br>(UNE-EN 1335-3:2009, 7.3.3)                                  | The base of the chair shall be secured on a rotating table so that the rotating axis of the chair coincides with the rotating axis of the table. The upper part of the chair shall be loosely fixed in such a way as not to hinder the rotation of the base. Load the seat in loading point A with a mass M <sub>1</sub> of 60 kg and in loading point C with a mass M <sub>2</sub> of 35 kg. The angle of rotation shall be 360° at a rate of (10±5) cycles/minute. Change direction after each rotation. Repeat the operation for 120000 cycles.   | PASS        |
| Foot rest durability<br>(UNE-EN 1335-3:2009, 7.3.4)                         | Apply a vertical downward force of 900 N to the foot rest at the point most likely to cause failure but not less than 80 mm from the front edge. For round cross section ring shaped foot rests, the force shall be applied through the centre of the ring cross section. Repeat the operation for 50000 cycles.   | NA          |



SGS-CSTC (China) Technical Services Co., Ltd.  
Anji Branch Harbin

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained herein reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No. 301, Sunlight Road, 2 Block, Sunlight Industry Zone, Anji County, Zhejiang Province, China 313300 t (86-572) 5018825 f (86-572) 5018829 www.sgs.com.cn  
中国·浙江·安吉县阳光工业园二区阳光大道301号 邮编:313300 t (86-572) 5018825 f (86-572) 5018829 e sgs.china@sgs.com

| Test Item  | Test Method & Test Requirement   | Test Result |
|--|--|-------------|
| Castor and chair base durability (UNE-EN 1335-3:2009, 7.3.5) | Not apply to chairs with castors which are braked when the chair is loaded.<br>The chair shall be placed on a rotating table so that the rotating axis of the chair coincides with the rotating axis of the table. Load the seat in point A with M <sub>1</sub> of 110 kg. The base shall be loosely fixed in such a way that there is no rotation of the base but that the natural movements of the castors are not prevented. The castors shall be left free to swivel, the table shall be rotated with a rate of 6 cycles per minute. The angle of rotation shall be from 0° to 180° and back. One rotation forward and one rotation backward constitutes one cycle. Repeat the operation for 36000 cycles. | PASS        |

**Remark:**

1. NA = Not applicable; NP = Not provided



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's Instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No. 301, Sunlight Road, 2 Block, Sunlight Industry Zone, Anji County, Zhejiang Province, China 313300 t (86-572) 5018825 f (86-572) 5018829 www.sgs.com.cn  
 中国·浙江·安吉县阳光工业园二区阳光大道301号 邮编:313300 t (86-572) 5018825 f (86-572) 5018829 e sgs.china@sgs.com

**Photo Appendix**



SGS authenticate the photo on original report only

\*\*\*End of Report\*\*\*



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.  
Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com  
No. 301, Sunlight Road, 2 Block, Sunlight Industry Zone, Anji County, Zhejiang Province, China 313300 t (86-572) 5018825 f (86-572) 5018829 www.sgs.com.cn  
中国·浙江·安吉县阳光工业园二区阳光大道301号 邮编:313300 t (86-572) 5018825 f (86-572) 5018829 e sgs.china@sgs.com